



Housing Number and Type of LED
See Chart Below

Light Distribution
2 - Type 2

Voltage
MV - 120-277V

Finish
GY - Gray

Nominal Color Temperature
NW - 4000K

Accessories/Options
HSS - House Side Shield
350 - 350mA Drive Current

LUMINAIRE DATA

STREET TYPE	WATTAGE	MODEL	POWER CONSUMPTION (W)	Luminous Flux (lumen)	Efficacy (lm/W)	BUG
LOCAL	HPS $70/100$ WATTS	EC1-6M-NW-350	29	3000	103	B1 UO G1
NEIGHBORHOOD COLLECTOR	HPS 150 WATTS	EC3-10M-NW-350	40	4700	118	B1 UO G1
MAJOR COLLECTOR & MINOR ARTERIAL	HPS 200 WATTS	EC7-20M-NW-350	90	9700	108	B1 UO G2
MAJOR ARTERIAL	HPS 250 WATTS	EC7-20M-NW-530	137	13300	97	B1 UO G3



City of Lake Oswego  
Engineering Division

Erica Rooney, P.E. City Engineer

LED ECobra-head  
STREET LIGHT

S5-02D

EFFECTIVE DATE: JANUARY 1, 2018

NOT TO SCALE

DRAWING NUMBER